

Charging cable with connector T2 Mode 3 Case C, Straight, 3m



General information

Part no.:	E-3291-030B
Type vehicle side	Type 2, free conductor end, AC 1-phase
Specification/Norm	IEC 62196-1, IEC 61851-1, IEC 62196-2

Charging connctor and charging plug

Arrangement of phases	1p+N+PE and PP+CP
Current	20A
Current control contacts	2A
Rated operating voltage	200-250V
Rated operating voltage contro	30V
Insulation voltage	500V
Mean time to failure MTTF	>10 000 connections without load

Charging connector and charging plug

information of protection	IP67/IPx9 not plugged in and without closure cap (in relation to the interior of the housing with the exception of external live parts) - IP54 overall test with closure cap (including external live parts)
IP-Protection	IP54 (IP67/IPx9)
Operating temperature range	-30°C - +50°C
Proximity circuit	680 Ohm
Contact surface material	Silver plated brass
Material of enclosure	strengthened thermo-shape material
Colour vehicle side	black

Charging cable

Charging capacity (kW)	3.7kW
Rated voltage	450/750V
Temperature resistance charging	-40°C to +80°C
Description of the charging ca	Halogen free, flame-resistant, high mechanical resistance, very good cold flexibility, very good oil and fuel resistance, UV-, ozone resistant and weatherproof
Cross-section current-carrying	3 x 2,5mm ²
Cross section signal conductor	1 x 0,50mm ²
Insulation conductors	EPR (3G) EVI-2 (DIN EN 50620)
Cord length	3m
Jacket material	TPE-U (11Y) EVM-1 (n. DIN EN 50620 acc. to DIN EN 50620)
Cable colour	black
Outer diameter D	10,0 ± 0,30 mm
Minimum bending radius static	4 x D
Minimum bending radius dynamic	7,5 x D
Handling	Incorrect use caused by torsional stress together with simultaneous expansion of cable should be avoided
Standards charging cable	ISO 4982-2, DIN EN 50363-10-2, DIN EN 50267-2-1, IEC 60228, DIN EN 50620, IEC 60332-1

Further cable lengths and individual colour adjustment on request.

Passing on to third parties only with the approval of Bals Elektrotechnik GmbH & Co. KG

Subject to technical modifications and typographical errors

Only valid at the time of printing. In case of recycling, check the current version.