

Charging socket Front mounting






Charging socket

Part no.:	E-80201-16
Protection degree installed	IP20
Arrangement of phases	3p+N+PE and PP+CP
Current	20A
Current control contacts	2A
Rated operating voltage	200/346-240/415VAC
Rated operating voltage contro	30V
Insulation voltage	500V
Mean time to failure MTTF	>10.000 plug-in cycles without load
Contact surface material	Ag
Connection design	Screw connection, conductor cross-section up to 4mm ² and 0.5mm ² for CP and PP
Material of enclosure	Strong thermo moulded material
Colour of appliance	Enclosure black RAL 9005

Actuator - Interlocking system

Number of poles actuator	3p
Nominal voltage	12V DC
Operating voltage actuator	9V - 15,5V DC
Maximum current consumption	3,2A
No load current	less than or equal to 250mA
Actuating time	200ms < t < 10s Voltage and temperature dependent not suitable for permanents power supply
Stability of stop position	#6° (with short-circuited motor)
Operating temperature range	-40°C to +85°C
Life time	60.000 switching cycles total
Assembly element	fixable push-together system
Connection for actuator	connecting cable with junction Type E-314-1000 (1000mm length – 3x0,5mm2) not included in the delivery

Connection table - Actuator



Exploded view

Further cable lengths and individual colour adjustment on request.

Passing on to third parties only with the approval of Bals Elektrotechnik GmbH & Co. KG

Subject to technical modifications and typographical errors

Only valid at the time of printing. In case of recycling, check the current version.

